

पिपिपि ईकाई, नेपालगंज

सोलार पोल, बस बिसौंनी र ट्राफिक पोष्ट निर्माण कार्यको अपेक्षित प्राबिधिक स्पेशिफिकेशन

(A) Solar pole specification

Solar pole: 9M (TOP Diameter 80 MM, Buttom Diameter 188mm)

वॉक

5003

- Thickness: 3.5MM
- Hot dip glavnised and power coating
- System must have ABP(Anti Bird Protection)
- Light 40 W, Battery LIFE PO4: 100AMP (3000 times rechargeable capacity)
- Controller- 30A12V , Solar 150W*4 (mono crystaline)

BOX SIZE

Over all size: W1200 X H2000MM Frame size: W1200 X H1800MM

Material : Glass FEBRIC Basket : Febric Molded

All the design should have with picture and above size

Option: from NEA System

B) Bus Shelter box and other specification

• Top front: 4000*1220mm;

Top side: 1500*1220mm;

Buttom: 3540*1500mm

• Side box :1000*1500mm;

Total Height :3520mm;

Thickness:3.5mm;

- Solar :150*4(mono crystaline)
- Controller: 30A12V; Battery: 150*2
- All the design should have with picture and above size
- Power: WW-3000,PW-6000,CW-8000K(38 Digree,IP-65,3030LED,DC12V,Luminous Flex:120-140lm)
- Hot dip glavnised and power coating
- Material: Light box:Steel
- Chair:Galvanized sheet+iron/Pipe+angle

Traffic Umbrella (Booth) C)

- Roof top light box galvanized sheet+30*30*2.0 steel + inside led light beads (side light) 66.4" 80mm
- Light box steel structure 30mm galvanized steel frame 66.4" 66.4"
- Structure pillar ø76*3 Support tube ø76mm 116.8" 3mm
- box (top) 1.2mm panel 60" 60" 16"
- box (down) 1.5mm galvanized panel+ø25*1.2 galvanized tube 60" 60" 30.78
- Base 6.0mm panel ø32" 12" and ø56" 8"
- All the design should have with picture and above size
- Hot dip glavnised and power coating
- Power: WW-3000,PW-6000,CW-8000K(38 Digree,IP-65,3030LED,DC12V,Luminous Flex:120-140lm)

नेपालगंज उपमहानगरपालिका



मार कार्यपालिकाको कार्यालय

पिपिपि ईकाई, नेपालगंज

सोलार पोल, बस बिसौंनी र ट्राफिक पोष्ट निर्माण कार्यको अपेक्षित प्राविधिक स्पेशिफिकेशन

Subject Heading SELECTION Criterias;

- Work experience in PPP Model with agreements copy and installation photos of different cities-
- 2. Technical document (drawing and quality) .
- 3. Company profile (workers and machine) .
- 4. 3 years tax clearance.
- 5. Black listed before or not letter.
- 6. International goods imported letter for PPP models (custom clearance letter with goods) or local purchase vat bill -
- 7. Technical Proposals and Financial proposals should have separately. At First, the Private Partner will be selected from technical proposals. If not selected from technical that company cannot participate in financial bidding.
- 8. Selected company can participate in Financial proposal. Both proposals should have separate seal pack and both proposal need to again seal pack together.